

## YDS-4G61W-073 SD-WAN 4G Router 1200M Dual Band New Arrival



Front View



Back View

### Product Overview

YDS-4G61W-073 is a 4G Wireless Router, which supports APP or WEB management, SD-WAN remote networking and Wi-Fi dual-bands, to make the network deployment more flexible.

It was designed with an aluminum alloy shell. It is suitable for offices without WAN, residences and factories with many wireless coverage requirements.

## YDS-4G61W-073 SD-WAN 4G Router 1200M Dual Band New Arrival

### Features

- Support APP and WEB Management
- Support SD-WAN Remote Networking
- Provide 5\*10/100/1000M Ethernet Port
- Support Automatic Adjustment of Wireless Transmission Rates
- Support All-network 4G
- Support 64/128 bits WEP Encryption, Encryption and Security Mechanisms such as WPA, WPA2, WPA-Hybrid. It can guarantee the security of data transmitted in wireless network
- Support SSID Broadcast Control and Effectively Prevent Leakage of SSID Broadcast

### Product Specification

<b>Chipset</b>	MT7621+MT7603+MT7613
<b>DRAM</b>	DDR3 256MByte
<b>FLASH</b>	16MByte
<b>Port</b>	1* 10/100/1000M WAN Port, 4* 10/100/1000M LAN Port, 1* Console Port.
<b>2.4G Data Rate</b>	300Mbps
<b>5.8G Data Rate</b>	867Mbps
<b>Modulation</b>	OFDM/BPSK/QPSK/CCK/DQPSK/DBPSK
<b>Standard</b>	IEEE802.11a,IEEE802.11n,IEEE802.11g,IEEE802.11b,IEEE802.3u,IEEE802.3af, IEEE802.11ac
<b>Channel</b>	2.4G 2412Mhz~2472Mhz / 5.8G 5180Mhz~5825Mhz
<b>Power Dissipation</b>	≤15W
<b>Power</b>	DC 12V 1.5A



## YDS-4G61W-073 SD-WAN 4G Router 1200M Dual Band New Arrival

### Product Specification

RF @25°C±2Db 2.4G	802.11b	20±2dBm		
	802.11g	6-24Mbps	20±2dBm	
		36-48Mbps	20±2dBm	
		54Mbps	20±2dBm	
	802.11n	HT20	MCS 7	20±2dBm
HT40		MCS 7	20±2dBm	
RF @25°C±2dB 5.8G	802.11a	6-24Mbps	20±2dBm	
		36-48Mbps	18±2dBm	
		54Mbps	17±2dBm	
	802.11ac	HT20	MCS 0-3	20±2dBm
			MCS 4	20±2dBm
			MCS 5	19±2dBm
			MCS 6	18±2dBm
			MCS 7	18±2dBm
	802.11ac	HT40	MCS 0-3	20±2dBm
			MCS 4	19±2dBm
			MCS 5	19±2dBm
			MCS 6	18±2dBm
	802.11ac	HT80	MCS 0-3	20±2dBm
			MCS 4	19±2dBm
			MCS 5	19±2dBm
			MCS 6	18±2dBm
			MCS 7	18±2dBm
WIFI Antenna	Frequency	2412 ~ 2487MHz		
	Antenna Port	SMA		
	Quantity	2		
	Gain	5DBi		
4G System	4G Antenna Port	SMA		
	4G Antenna Quantity	2		
	4G Antenna Gain	5DBi		
	Frequency Band Information			



## YDS-4G61W-073 SD-WAN 4G Router 1200M Dual Band New Arrival

### Product Specification

	Band Configuration	GSM900/1800+TDD B38/39/40/41+FDD B1/3/8+WCDMA B1/8+TDS B34/39	
	Data Transmission Rate (Maximum)	TDD	3GPP R9 CAT4 downlink speed 150Mbps, uplink speed 50Mbps
		FDD	3GPP R9 CAT4 downlink speed 150Mbps, uplink speed 50Mbps
		TD-SCDMA	downlink speed 2.8Mbps, uplink speed 2.2Mbps
		WCDMA	3GPP R7 downlink speed 21Mbps, uplink speed 5.76Mbps
		EDGE	Class12, downlink speed 236.8kbps, uplink speed
		GPRS	Class10, downlink speed 85.6kbps, uplink speed
Card Slot	SIM Card Slot *1		
Management	WEP Management	Yes	
	APP Management	Yes	
	SNMP MIB	Yes	
	Telnet	Yes	
	Serial	Yes	
Security	MAC Address Control	No	
	Encryption	WEP 64/128bits,WPA,WPA2,802.1x	

**YDS-4G61W-073**  
**SD-WAN 4G Router 1200M Dual Band New Arrival**

### Product Specification

<b>Operating/Storage Environment</b>	Operating Temperature	-30 ~ 65°C
	Storage Temperature	-50 ~ 80°C
	Humidity (non-condensed)	≤95% (Non-condensed)
<b>Product Size</b>	Size: 145*105*45mm	
	Weight: 0.35kg (Without Accessories)	
<b>Packing List</b>	4 Antennas (WIFI*2, 4G*2)	
	1 Power Supply	
	1 Manual	



## YDS-4G61W-073 SD-WAN 4G Router 1200M Dual Band New Arrival

