

YDS-DIP1526-H-057 Wireless Access Point Bridge For Long Range Transmission



Front View



Back View

Product Overview

YDS-DIP1526-H-057 is a 5.8GHz wireless bridge, which can easily complete point-to-point or point-to-multiple devices pairing through DIP switches, no need to log in to the page to set up.

The wireless speed can up to 150Mbps and it can prevent from the weather, dust and the sun with the IP65 protection level shell. It is mainly used in warehouse, construction site, factory monitoring and other places.

Features

- DIP Settings is more convenient to use
- Easy installation, support pole mounting
- Support PoE 24V Power Supply
- Support IEEE 802.11 b/g/n Protocol
- Wireless Speed Up to 150Mbps
- IP65 Shell Level can Prevent From the Weather, Dust and the Sun
- Excellent Transmitting Power and Receiving Sensitivity



YDS-DIP1526-H-057 Wireless Access Point Bridge For Long Range Transmission

Product Specification

Chipset	Atheros AR9344 600MHz				
DRAM	DDR2 64MByte				
FLASH	8MByte				
IC	SKY85735				
Wired Port	10/100Mbps LAN*2				
Speed	11a:54M,48M,36M,24M,18M,12M,9M,6Mbps				
	11n:7.2M,14.4M,21.7M,28.9M,43.3M,57.8M,65M,72.2M,14.4M,				
	28.9M,43.3M,57.8M,86.7M,115.6M,130M,144.4、150Mbps				
Transmission	DSSS				
Modulation	OFDM/BPSK/QPSK/CCK/DQPSK/DBPSK				
Standard	IEEE802.11n,IEEE802.11a ,IEEE802.3u				
Protocol	CSMA/CA,TCP/IP,IPX/SPX, NetBEUI, DHCP,NDIS3,NDIS4,NDIS5				
Channel	4900 ~ 6100MHz				
Power Dissipation	≤3W				
Power	POE24V 1A(default)/ 48V 0.5A				
RF @25°C±2dB	802.11a	6-24Mbps		23±2dBm	
		36-48Mbps		22±2dBm	
		54Mbps		21±2dBm	
	802.11n	HT20	MCS 0-3		23±2dBm
			MCS 4		22±2dBm
			MCS 5		21.5±2dBm
			MCS 6		21±2dBm
			MCS 7		20.5±2dBm
		HT40	MCS 0-3		22±2dBm
			MCS 4		21.5±2dBm
	MCS 5		21±2dBm		
		MCS 6		20.5±2dBm	
		MCS 7		20±2dBm	



YDS-DIP1526-H-057 Wireless Access Point Bridge For Long Range Transmission

Product Specification

Sensitivity	802.11a	6Mbps ≤ -89; 54Mbps ≤ -73	
	802.11n	HT20	MCS 0 ≤ -86; MCS 7 ≤ -68
		HT40	MCS 0 ≤ -83; MCS 7 ≤ -65
Antenna	Frequency	4900 ~ 6100MHz	
	Polarization	Vertical	
	Gain	12DBi	
Management	WEP Management	Yes	
	SNMP MIB	Yes	
	Telnet	Yes	
	Serial	Yes	
Security	MAC Address Control	No	
	Encryption	WEP 64/128bits,WPA,WPA2,802.1x	
Operating Condition	Operating Temperature	-30 ~ 65°C	
	Storage Temperature	-50 ~ 80°C	
	Humidity	≤95%(non-condensed)	
Product Size	Size: 205*205*132.3MM		
	Weight: 0.5kg		
Packing List	1 Pole Bracket		
	1 Bracket Lock		
	4 Screws		
	4 Rubber Plugs		
	1 Power Supply		
	1 Wall Hanging		
	1 Stainless Steel Fixed Ring		
	1 Specification		

YDS-DIP1526-H-057
Wireless Access Point Bridge For Long Range Transmission



YDS-DIP1526-H-057 Wireless Access Point Bridge For Long Range Transmission

