

## YDS-DIP1526-HW-48-058 Wireless Access Point Bridge For Long Range Transmission



Front View



Back View

### Product Overview

YDS-DIP1526-HW-48-058 is a 5.8GHz wireless bridge, which can easily complete point-to-point or point-to-multiple devices pairing through DIP switches, no need to log in to the page to set up.

The wireless speed can up to 150Mbps and it can prevent from the weather, dust and the sun with the IP65 protection level shell.

It is mainly used in warehouse, construction site, factory monitoring and other places.

### Features

- DIP Settings is more convenient to use
- Easy installation, support pole mounting
- Support PoE 48V or DC12V Power Supply
- Support IEEE 802.11 b/g/n Protocol
- Wireless Speed Up to 150Mbps
- IP65 Shell Level can Prevent From the Weather, Dust and the Sun
- Excellent Transmitting Power and Receiving Sensitivity



## YDS-DIP1526-HW-48-058 Wireless Access Point Bridge For Long Range Transmission

### Product Specification

<b>Chipset</b>	Atheros AR9344 600MHz				
<b>DRAM</b>	DDR2 64MByte				
<b>FLASH</b>	8MByte				
<b>IC</b>	SKY85735				
<b>Wired Port</b>	10/100Mbps LAN*2				
<b>Speed</b>	11a:54M,48M,36M,24M,18M,12M,9M,6Mbps				
	11n:7.2M,14.4M,21.7M,28.9M,43.3M,57.8M,65M,72.2M,14.4M,				
	28.9M,43.3M,57.8M,86.7M,115.6M,130M,144.4、150Mbps				
<b>Transmission</b>	DSSS				
<b>Modulation</b>	OFDM/BPSK/QPSK/CCK/DQPSK/DBPSK				
<b>Standard</b>	IEEE802.11n,IEEE802.11a ,IEEE802.3u				
<b>Protocol</b>	CSMA/CA,TCP/IP,IPX/SPX, NetBEUI, DHCP,NDIS3,NDIS4,NDIS5				
<b>Channel</b>	4900 ~ 6100MHz				
<b>Power Dissipation</b>	≤3W				
<b>Power</b>	48V 0.5A/DC12V 1A				
<b>RF</b> @25°C±2dB	802.11a	6-24Mbps		23±2dBm	
		36-48Mbps		22±2dBm	
		54Mbps		21±2dBm	
	802.11n	HT20	MCS 0-3		23±2dBm
			MCS 4		22±2dBm
			MCS 5		21.5±2dBm
			MCS 6		21±2dBm
		HT40	MCS 7		20.5±2dBm
			MCS 0-3		22±2dBm
			MCS 4		21.5±2dBm
			MCS 5		21±2dBm
MCS 6		20.5±2dBm			
MCS 7		20±2dBm			



## YDS-DIP1526-HW-48-058 Wireless Access Point Bridge For Long Range Transmission

### Product Specification

<b>Sensitivity</b>	802.11a	6Mbps ≤ -89; 54Mbps ≤ -73	
	802.11n	HT20	MCS 0 ≤ -86; MCS 7 ≤ -68
		HT40	MCS 0 ≤ -83; MCS 7 ≤ -65
<b>Antenna</b>	Frequency	4900 ~ 6100MHz	
	Polarization	Vertical	
	Gain	12DBi	
<b>Management</b>	WEP Management	Yes	
	SNMP MIB	Yes	
	Telnet	Yes	
	Serial	Yes	
<b>Security</b>	MAC Address Control	No	
	Encryption	WEP 64/128bits,WPA,WPA2,802.1x	
<b>Operating Condition</b>	Operating Temperature	-30 ~ 65°C	
	Storage Temperature	-50 ~ 80°C	
	Humidity	≤95%(non-condensed)	
<b>Product Size</b>	Size: 205*205*132.3MM		
	Weight: 0.5kg		
<b>Packing List</b>	1 Pole Bracket		
	1 Bracket Lock		
	4 Screws		
	4 Rubber Plugs		
	1 Power Supply		
	1 Wall Hanging		
	1 Stainless Steel Fixed Ring		
	1 Specification		

**YDS-DIP1526-HW-48-058**  
**Wireless Access Point Bridge For Long Range Transmission**



**YDS-DIP1526-HW-48-058**  
**Wireless Access Point Bridge For Long Range Transmission**

