

YDS-DIP9526K-HW-48-062 Wireless Access Point Bridge For Long Range Transmission



Front View



Back View

Product Overview

YDS-DIP9526-HW-48-062 is a 5.8GHz wireless bridge, which can easily complete point-to-point or point-to-multiple devices pairing through DIP switches, no need to log in to the page to set up.

The wireless speed can up to 867Mbps and it can prevent from the weather, dust and the sun with the IP65 protection level shell.

It is mainly used in warehouse, construction site, factory monitoring and other places.

Features

- DIP Settings is more convenient to use
- Easy installation, support pole mounting
- Support PoE 24V Power Supply
- Support IEEE 802.11 b/g/n/ac Protocol
- Wireless Speed Up to 867Mbps
- IP65 Shell Level can Prevent From the Weather, Dust and the Sun
- Excellent Transmitting Power and Receiving Sensitivity



YDS-DIP9526K-HW-48-062 Wireless Access Point Bridge For Long Range Transmission

Product Specification

Chipset	QCA9563+ QCA9886				
DRAM	DDR2 128MByte				
FLASH	16MByte				
IC	SKY85728*2				
Wired Port	10/100/1000Mbps LAN*2				
Speed	867Mbps				
Modulation	OFDM: BPSK, QPSK, 16-QAM, 64-QAM, 256QAM, DBPSK, DQPSK, CCK				
Standard	IEEE802.11a,IEEE802.11n,IEEE802.3u,IEEE802.11ac				
Channel	5180Mhz~5825Mhz				
Power Dissipation	≤7W				
Power	POE 48V 0.5A				
RF @25°C±2dB	802.11a	6-24Mbps		26±2dBm	
		36-48Mbps		25±2dBm	
		54Mbps		24±2dBm	
	802.11ac	HT20	MCS 0-3		26±2dBm
			MCS 4		25±2dBm
			MCS 5		24.5±2dBm
			MCS 6		24±2dBm
			MCS 7		23.5±2dBm
	802.11ac	HT40	MCS 0-3		25±2dBm
			MCS 4		24.5±2dBm
			MCS 5		24±2dBm
			MCS 6		23.5±2dBm
			MCS 7		23±2dBm
	802.11ac	HT80	MCS 0-3		18±2dBm
			MCS 4		18±2dBm
MCS 5			18±2dBm		
MCS 6			18±2dBm		
MCS 7			16±2dBm		



YDS-DIP9526K-HW-48-062 Wireless Access Point Bridge For Long Range Transmission

Product Specification

Sensitivity	802.11a	6Mbps ≤ -89; 54Mbps ≤ -73	
	802.11ac	HT20	MCS 0 ≤ -94; MCS 7 ≤ -76
		HT40	MCS 0 ≤ -92; MCS 7 ≤ -76
		HT80	MCS 0 ≤ -90; MCS 7 ≤ -67
Antenna	Frequency	4900 ~ 6100MHz	
	Polarization	Vertical / Horizontal	
	Gain	16DBi	
Management	WEP Management	Yes	
	SNMP MIB	Yes	
	Telnet	Yes	
	Serial	Yes	
Security	Encryption	WEP 64/128bits,WPA,WPA2,802.1x	
Operating Condition	Operating Temperature	-30 ~ 65°C	
	Storage Temperature	-50 ~ 80°C	
	Humidity	≤95%(non-condensed)	
Product Size	Size: 205*205*132.3MM		
	Weight: 0.5kg		
Packing List	1 Power Supply		
	1 Stainless Steel Fixed Ring		
	1 Pole Bracket		
	1 Bracket Lock		
	1 Wall Hanging		
	4 Screws		
	1 Rubber Plug		
	1 Specification		

YDS-DIP9526K-HW-48-062
Wireless Access Point Bridge For Long Range Transmission



YDS-DIP9526K-HW-48-062
Wireless Access Point Bridge For Long Range Transmission

