

**YDS-MRT20 V20.11-078
Dual-band Wi-Fi Repeater 1200Mbps Waterproof High
Frequency Extender**



Front View



Back View

Product Overview

YDS-MRT20 V20.11-078 is a outdoor Wi-Fi dual-band repeater, which can supports up to 1200Mbps commercial AP coverage or home Wi-Fi coverage, stable signal and simple configuration.

It is suitable for the expansion of Wi-Fi signal in villa, compound building, large family environment, etc. It can effectively solve the problem of blind area of signal, and it is an intelligent product of large family housing

YDS-MRT20 V20.11-078 Dual-band Wi-Fi Repeater 1200Mbps Waterproof High Frequency Extender

Features

- Wi-Fi Dual-band In-one
- Wireless transmission speed up to 1200 Mbps, 2.4GHz up to 300 Mbps, 5GHz up to 867 Mbps
- Support Tuya APP
- Covering Area is Radius 85M & Carrying Capacity is 65 Users
- Transmitting Power is 23dBm & Antenna Gain is 5DBi
- Stable Signal & Simple Configuration

Product Specification


Chipset	MT7628+MT7613
Flash	8 MB
RAM	64 MB
Wi-Fi	IEEE 802.11a/b/g/n/ac/ac(wave2) Wireless Protocol
	Maximum Wireless Rate 1167Mbps (2.4GHz 300Mbps, 5GHz 867Mbps)
	Wireless Frequency: 2.4 GHz和 5 GHz
	2×2 MIMO
	WMM: Priority based data processing and forwarding
	Wi-Fi Dual-band in-one
	Repeat Extension Function
Antenna	Built-in Antenna: 2*2.4G & 2*5G Antenna
Support Data Rate (Mbps)	
Standard	Data Rates/ Data Rate
802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n	6.5 Mbps to 450 Mbps (MCS0 - MCS23, HT 20/40)
802.11ac	6.5 Mbps to 1.2 Gbps (MCS0 □ MCS9 NSS1/2/3/4, VHT 20/40/80)
	58 Mbps to 1.2 Gbps (MCS0 □MCS9 NSS1/2, VHT 160)

YDS-MRT20 V20.11-078 Dual-band Wi-Fi Repeater 1200Mbps Waterproof High Frequency Extender

Product Specification

802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps
Ethernet Port	1个10/100Mbps adaptive Ethernet Port
Software Function	Repeater
	SSID and Password Modification
	Terminal Management
	Tuya APP Configuration
	Wireless Speed-limiting
	Indicator Switch
	Wireless Plan
	Configuration Backup
	Local Online Upgrade
Management	WEB Management/ TELNET / SSH
	APP Management
Security	WPA-PSK、 WPA2-PSK Wireless Encryption
Power	DC 12V 1A
Operating Condition	Operating Temperature: -30°C to 65°C
	Storage Temperature: -40°C to 70°C
	Operating Temperature: 10% to 90%RH (non-condensed)
	Storage Temperature: 5% to 90%RH (non -condensed)
Product Size	Bare Size (Length×Width×Height) : 176*96*70.5MM
	Bare Weight: 0.3kg(Single Unit, Excluding Accessories and Packaging)

YDS-MRT20 V20.11-078
Dual-band Wi-Fi Repeater 1200Mbps Waterproof High
Frequency Extender



YDS-MRT20 V20.11-078
Dual-band Wi-Fi Repeater 1200Mbps Waterproof High
Frequency Extender

