

**YDS-MRT45 V40.1-082
Outdoor Wi-Fi 6 AP 1800Mbps Transmission Rate Dual-Band MESH
Routers POE Power Supply**



Front View



Back View

Product Overview

YDS-MRT45 V40.1-082 is a Wi-Fi 6 developed by Todaair, which can support up to 1800Mbps commercial AP coverage or home Wi-Fi coverage MESH routers.

Supports desktop placement, ceiling mounting and outdoor wall hanging waterproof installation


YDS-MRT45 V40.1-082 Outdoor Wi-Fi 6 AP 1800Mbps Transmission Rate Dual-Band MESH Routers POE Power Supply

Features

- Support 802.11 b/g/n/ac/ax 2x2:2
- Support 802.11 a/n/ac/ax 2x2:2
- 2 * 1000Mbps RJ45
- IEEE802.3at/af
- Weatherproof and anti-UV
- Dual frequency gigabit, support Wi-Fi 6
- Cloud management, intelligent operation and maintenance
- Support for outdoor scenario use
- Operating Temperature: - 30°C~ 50°C
- The WAN port supports POE function

Product Specification


Chipset	MT7621AT/A+MT7975DN+MT7905DN
DRAM	DDR3 128MByte
FLASH	16MByte
Power Amplifier IC	2.4G / 5.8G MT7905DN
Wired Interface	10/100/1000Mbps WAN*1 (POE) LAN*1
Date Rate 2.4G	580Mbps
Date Rate 5.8G	1201Mbps
Modulation Mode	OFDM/BPSK/QPSK/CCK/DQPSK/DBPSK
Standard	IEEE802.11a,IEEE802.11n,IEEE802.11g,IEEE802.11b,IEEE802.3u,IEEE802.3af, IEEE802.11ac,IEEE 802.11ax
Frequency Range	2.4G 2412Mhz~2472Mhz / 5.8G 5180Mhz~5825Mhz



YDS-MRT45 V40.1-082 Outdoor Wi-Fi 6 AP 1800Mbps Transmission Rate Dual-Band MESH Routers POE Power Supply

Product Specification

Power Consumption	≤15W				
Power	POE 48V				
RF Power @25°C±2Db 2.4G	802.11b	20±2dBm			
	802.11g	6-24Mbps	20±2dBm		
		36-48Mbps	20±2dBm		
		54Mbps	20±2dBm		
	802.11n	HT20	MCS 7	20±2dBm	
		HT40	MCS 7	20±2dBm	
	802.11ax	HT20	MCS0/12		
		HT40	MCS2/14		
	RF Power @25°C±2dB 5.8G	802.11a	6-24Mbps	20±2dBm	
			36-48Mbps	18±2dBm	
54Mbps			17±2dBm		
802.11ac		HT20	MCS 0-3	20±2dBm	
			MCS 4	20±2dBm	
			MCS 5	19±2dBm	
			MCS 6	18±2dBm	
			MCS 7	18±2dBm	
		HT40	MCS 0-3	20±2dBm	
			MCS 4	19±2dBm	
			MCS 5	19±2dBm	
MCS 6			18±2dBm		



YDS-MRT45 V40.1-082 Outdoor Wi-Fi 6 AP 1800Mbps Transmission Rate Dual-Band MESH Routers POE Power Supply

Product Specification

RF Power @25°C±2dB 5.8G	802.11ac	HT80	MCS 3	20±2dBm
			MCS 4	19±2dBm
			MCS 5	19±2dBm
			MCS 6	18±2dBm
			MCS 7	18±2dBm
	802.11ax	HT80	MCS0/12	17±2dBm
			MCS6/18	17±2dBm
Sensitivity 2.4G	IEEE 802.11b	11Mbps ≤ -85dBm		
	IEEE 802.11g	54Mbps ≤ -70dBm		
	802.11n	HT20	MCS 7 ≤ -65dBm	
		HT40	MCS 7 ≤ -62dBm	
Sensitivity 5.8G	802.11a	6Mbps ≤ -89; 54Mbps ≤ -73		
	802.11ac	HT20	MCS 0 ≤ -94; MCS 7 ≤ -76	
		HT40	MCS 0 ≤ -92; MCS 7 ≤ -76	
		HT80	MCS 0 ≤ -90; MCS 7 ≤ -67	
	802.11ax	HT80	MCS0 ≤ -85; MCS 12 ≤ -60	
Antenna System	Frequency Range	2.4G Antenna 2412Mhz~2484Mhz 5.8G Antenna 5150Mhz~5850Mhz		
	Polarization	Onmidirectional		
	Gain	4DBi*4		

YDS-MRT45 V40.1-082
Outdoor Wi-Fi 6 AP 1800Mbps Transmission Rate Dual-Band MESH
Routers POE Power Supply

Product Specification

Operating/Storage Environment	Operating Temperature	-30 ~ 50°C
	Storage Temperature	-50 ~ 80°C
	Humidity(Non-concentrated)	≤95% (Non-condensed)
Size & Weight	Bare Metal Size: 70*170mm	
	Bare Weight: 0.45kg	
Packing List	1 Power Supply	
	1 Specification	
	1 Net Cable	
	2 Plastic Cable Ties	
	2 Screws	
	2 Rubber Plugs	

YDS-MRT45 V40.1-082
Outdoor Wi-Fi 6 AP 1800Mbps Transmission Rate Dual-Band MESH
Routers POE Power Supply



**YDS-MRT45 V40.1-082
Outdoor Wi-Fi 6 AP 1800Mbps Transmission Rate Dual-Band MESH
Routers POE Power Supply**

