

YDS-POE29-RX548G-SFP-085 Outdoor Waterproof Unmanaged 4 Ports Full Gigabit 1000Mbps POE Network Switch For POE Camera



Front View



Back View

Product Overview

YDS-POE29-RX548G-SFP-085 is an outdoor dedicated Gigabit switch, it can prevent from the weather, dust and the sun with the IP65 protection level shell.

It is mainly used in farms, factories, fish ponds, highway monitoring and other places.

Features

- 5*1000Mbps RJ45-Port and 1*1000Mbps SFP Uplink Optical Port
- 1-4 Port support IEEE 802.3af/at Standard PoE Power Supply
- Max PoE Output Power up to 60W
- Professional Outdoor Shell Design; IP65 Shell Level can Prevent From the Dust and the Water
- Easy installation, supports wall-mount and pole-mount

YDS-POE29-RX548G-SFP-085
Outdoor Waterproof Unmanaged 4 Ports Full Gigabit 1000Mbps POE
Network Switch For POE Camera

Product Specification

Chipset	QCA8337+RTL8234
Port	4*10/100/1000Mbps POE Port(Standard 48V Power Supply), 1*10/100/1000 Mbit/s Uplink network port, 1 1*10/100/1000Mbps SFP Uplink Optical Port
	Support 4 Ports IEEE802.3af/at Standard PoE Power Supply
Power	Power Input Voltage: AC 100-220V 50-60Hz
	Single Port Maximum Power: 30W
	Power Consumption: 4W
	Maximum Power Consumption: 60W
Performance	Backplane Bandwidth: 12Gbps
	Packet Forwarding Speed : 11.9Mpps
	All Ports Line Speed Forwarding
	The Size of the MAC Address Table: 4K
	Auto MDI/MDI-X: Yes
Standard	IEEE802.3、IEEE802.3u、IEEE802.3ab、IEEE802.3x、IEEE802.3af、IEEE802.3at
Operating Condi- tion	Operating Temperature: -20-60°C
	Storage Temperature: -50 ~ 80°C
	Operating Humidity: ≤10~90%(non-condensed)
	Storage Humidity: ≤5~90%(non-condensed)
Product Size	Size: 300*220*30mm
	Weight: 1.2kg
Packing List	2 Stainless Steel Fixed Rings
	1 Specification

YDS-POE29-RX548G-SFP-085
Outdoor Waterproof Unmanaged 4 Ports Full Gigabit 1000Mbps POE
Network Switch For POE Camera

